

FITTINGS & ACCESSORIES

FITTINGS

PVC PIPES

Type in mm	20	25	32	40	50	63	75	90	110	125	140	160	200	225	250	315
Diameter in mm	20	25	32	40	50	63	75	90	110	125	140	160	200	225	250	315
Length in meter	5	5	5	5	5	6	6	6	6	6	6	6	6	6	6	6
Wall thickness/mm	1,5	1,5	1,8	1,9	2,4	3	3,6	4,3	3,2	3,7	4,1	4,7	5,9	6,6	7,3	9,2
Max. Working bar	16	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
Bar option	-	-	-	-	-	-	-	-	6	6	6	6	6	6	6	6

DIN standard: DIN 8061 and 8062

Colour: RAL 7011 (grey)

WELLDANA® SOFT FLEX HOSE

Type/In mm	20	32	40	50	63	75
Diameter in mm. OD	20	32	40	50	63	75
Length meter in roll	25	25	25	25	25	25
Wall thickness in mm	2,25	3,5	4	4	4	6
Max. working pressure in bar	8	7	7	7	7	6
Max. working temperature °C	45	45	45	45	45	45

Measurement tolerances: ± 1 %

Resistants to chlorine: max 3 %